

Product Fiche Alfea Extensa Duo Al6 R32 WOYA060KLT

Model(s): Alfea Extensa Duo Al 6. R32

Outdoor unit reference: WOYA060KLT

Air / water heat pump: Yes
Equipped with a backup heater Yes

Equipped with a backup heater	Yes			
Temperature control	Variable Outlet			
Parameters are declared for:	Low & High temperature applications			
Parameters are declared for:	Average Climate conditions			
Heating aplications			35°C	55°C
EN14825 - Space heating				
Energy class (product & package)	-	-	A+++	A++
Rated heat output (*)	Prated	kW	6	5
Rated energy efficiency	ns	%	175	125
Declared heat output with a partial load for an indoor temperature of 20°C and an outdoor				
temp. of Tj				
Tj = -7°C = Bivalent temperature	Pdh	kW	5.00	4.70
Tj = +2°C	Pdh	kW	3.00	2.90
Tj = +7°C	Pdh	kW	2.10	1.80
Tj = + 12 °C	Pdh	kW	2.40	2.30
Tj = bivalent temperature	Pdh	kW	5.00	4.37
Tj = operating temperature	Pdh	kW	4.50	4.00
Degradation coefficient (**)	Cdh	-	0.96	0.97
Declared coefficients of performance with a partial load for an indoor temperature of 20°C				
and an outdoor temp. of Tj				
Tj = -7°C = Bivalent temperature	COPd	-	2.74	1.97
Tj = +2°C	COPd	-	4.68	3.11
Tj = +7°C	COPd	-	6.04	4.29
Tj = + 12 °C	COPd	-	7.43	6.06
Tj = bivalent temperature	COPd	-	2.74	1.97
Tj = operating temperature	COPd	-	2.67	1.73
Operating temperature limit	TOL	°C	-10	
Maxoperating temperature	WTOL	°C	55	
Backup heater				
Rated heat output (*) (Electric)	Psup	kW	1.10	1.30
Annual Energy consumption	Qhe	kWhr	2594	3411
Electricity consumption in modes				
Shutdown	Poff	W	4	
Thermostat	Pto	W	12	13
Standby	Psb	W	10	
Acoustic data				
Sound Power Level of Outdoor unit	Lwa	dB (A)	57	
Sound Power Level of Indoor unit	Lwa	dB (A)	40	
EN16147- Domestic Hot Water production				
Declared Load profile	-	-	L	
Energy class (product & package)		-	A+	
Water Heating efficiency	nwh	%	130	
COP			3.1	
Reference Hot Water Temp		°C	54	
Standby Heat Loss		kWhr/day	2.12	
Volume of Water accounted for in test		Litre	245	ı